



## Technical data

Lenght overall	6.62 m
Inside lenght	5.53 m
Beam overall	2.70 m
Inside Beam	1.55 m
Tube diameter	50-61 cm
Separate chambers	5
Tube Material	Hypalon neoprene
CE Category	C
Maximum number of persons	13
Recommended engine power (max)	225 (230) hp 1 XXL - 2 XL
Fuel tank	260 lt in inox
Hull material	VTR (in sandwich PVC)
Hull Weight	810kg

## Standard Equipment

- Console with stainless steel black hand rail;
- Windscreen;
- Hydraulic steering and wheel;
- Switch panel;
- Navigation LED lights;
- Battery box and battery switch;
- Marine compass;
- GRP leaning post;
- Fuel system with blower and solenoid valve;
- Automatic bilge pump;
- 4 suspension hooks;
- Stainless steel ladder;
- V-shape GRP bow roller



## Optional

- GRP leaning post "LP9" with rear bench;
- Foldable seat for consolle on rear bench;
- Foldable table for GRP leaning post;
- GRP bench "BS9" with cuscion and backrest;
- GRP bench "BS compact" with foldable seats;
- Livewell kit for LP9;
- Livewell kit on the ground;
- Stern platform with stainless steel ladder;
- Black painted aluminium T-top
- Additional locker on the ground with heavy duty hatch
- Stainless steel water ski towing pole;
- Stainless steel roll bar;
- Stainless steel bottle rack 4/6;
- GRP small platform on tube;
- GRP small platform on tube;
- GRP Jockey seat "JS 100";
- Battery charger with cable 10mt
- Console cover;
- Leaning post cover;
- Bench cover.
- Big cleet on stern

