



Technical data

Lenght overall	8.44 m
Inside lenght	6.99 m
Beam overall	3.02 m
Inside Beam	1.86 m
Tube diameter	56 cm
Separate chambers	7
Tube Material	Hypalon neoprene
CE Category	C - B
Maximum number of persons	22
Recommended engine power (max)	350 (400) hp 1XXL – 2XL
Fuel tank	500 lt in inox
Hull material	VTR (in sandwich PVC)
Hull Weight	1050 kg

Standard Equipment

- Consolle with stainless steel black hand rail;
- Windscreen;
- Idraulic steering and wheel;
- Switch panel;
- Navigation LED lights;
- Battery box and battery switch;
- Marine compass;
- GRP leaning post;
- Fuel system with blower and solenoid valve;
- Automatic bilge pump;
- 4 sospension hooks;
- Stainless steel ladder;
- V-shape GRP bow roller .



Optional

- GRP leaning post "LP11" with rear bench;
- Foldable seat for consolle on rear bench;
- Foldable table for GRP leaning post;
- GRP bench "BS119" with cuscion and backrest;
- GRP bench "BS compact" with foldable seats;
- Livewell kit for LP11;
- Livewell kit on the ground;
- Stern platform with stainless steel ladder;
- Black painted aluminium T-top
- Additional locker on the ground with heavy duty hatch
- Stainless steel water ski towing pole;
- Stainless steel roll bar;
- Stainless steel bottle rack 4/6;
- GRP small platform on tube;
- GRP small platform on tube;
- GRP Jockey seat "JS 100";
- Battery charger with cable 10mt
- Big cleet on stern
- Electric anchor winch
- Console cover;
- Leaning post cover;
- Bench cover.

